

CARLISLE

branded tires are now

CARLSTAR



CONSTRUCTION / INDUSTRIAL

TIRE CATALOG






CONSTRUCTION / INDUSTRIAL

Construction and industrial tires used to be manufactured under the name Carlisle has been workhorses of American industry for decades. Applications for skid steer, backhoe, telescopic loader, forklift and more. From 2023 they are getting a new brand name after their original manufacturing company: CARLSTAR

TREAD VIEW QUICK REFERENCE GUIDE



GROUND FORCE 700

Backhoe loader, industrial tractors

Ground Force 700 is a radial backhoe tire designed for greater load capacity and more comfortable ride versus traditional bias backhoe tires. Increased tread depth, puncture-resistant steel belts, and multiple tread options make this the tire of choice for operators looking to get the most out of their backhoe or utility tractor.



Item number	Size	LI/SI	Tube Type	ECE	Rim Width (inch)	Mounted Diameter (mm)	Mounted Width (mm)	Max Load (kg)	Rated Speed (km/h)	Inflation Pressure (bar)	Tread depth (mm)	Weight (kg)	CoO	EAN
6X15413	280/80R18 (10.5/80R18)	132A8/B	TL	YES	9	914	287	2000	50	4	28	38.5	CN	5999110833446
6X15421	340/80R18 (12.5/80R18)	143A8/B	TL	YES	11	996	353	2725	50	4	30	57.5	CN	5999110833453
6X15431	400/70R18 (40S/70R18)	147A8/B	TL	YES	13	1020	409	3075	50	4	33	63.5	CN	5999110833460
6X15441	280/80R20 (10.5/80R20)	133A8/B	TL	YES	9	967	285	2060	50	4	28	41.5	CN	5999110833477
6X15451	340/80R20 (12.5/80R20)	144A8/B	TL	YES	11	1053	356	2800	50	4	30	61.5	CN	5999110833484
6X15461	380/75R20 (14.5R20)	148A8/B	TL	YES	12	1088	386	3150	50	4	33	65.5	CN	5999110833491
6X15471	400/70R20 (16.0R20)	149A8/B	TL	YES	13	1072	409	3250	50	4	33	69.5	CN	5999110833507
6X15651	400/70R20 (16.0R20) ST	149A8/B	TL	YES	13	1072	409	3250	50	4	33	74.5	CN	5999110833620
6X15481	400/70R24 (16.0R24)	152A8/B	TL	YES	13	1172	406	3550	50	4	33	80.5	CN	5999110833514
6X15491	440/80R24 (16.9R24)	161A8/B	TL	YES	14	1312	457	4625	50	4	36	110.5	CN	5999110833521
6X15501	460/70R24 (17.5LR24)	159A8/B	TL	YES	15	1247	467	4375	50	4	36	101	CN	5999110833538
6X15511	500/70R24 (19.5LR24)	164A8/B	TL	YES	16	1317	506	5000	50	4	36	115.5	CN	5999110833545
6X15521	480/80R26 (18.4R26)	160A8/B	TL	YES	15	1412	498	4500	50	3.2	36	130	CN	5999110833552
6X15103	440/80R28 (16.9R28)	156A8/B	TL	YES	14	1416	457	4000	50	3.2	36	121.5	CN	5999110833569

ST = Steel Belt

GROUND FORCE 700 MX

Backhoe loader, industrial tractors

Ground Force 700 is a radial backhoe tire designed for greater load capacity and more comfortable ride versus traditional bias backhoe tires. Increased tread depth, puncture resistant steel belts, and multiple tread options make this the tire of choice for operators looking to get the most out of their backhoe or utility tractor.



Item number	Size	LI/SI	Tube Type	ECE	Rim Width (inch)	Mounted Diameter (mm)	Mounted Width (mm)	Max Load (kg)	Rated Speed (km/h)	Inflation Pressure (bar)	Tread depth (mm)	Weight (kg)	CoO	EAN
6X15143	40S/70R18 (16/70R18)	141B	TL	YES	13	1025	401	2575	50	4	26	68.5	CN	5999110833576
6X15153	40S/70R20 (16/70R20)	149A8/B	TL	YES	13	1076	404	3250	50	4	26	74.5	CN	5999110833583
6X15023	460/70R24 (17.5LR24)	159A8/B	TL	YES	15	1250	462	4375	50	4	28	111	CN	5999110833590
6X15113	500/70R24 (19.5LR24)	164A8/B	TL	YES	16	1310	503	5000	50	4	28	124	CN	5999110833606

GROUND FORCE 717

Backhoe, Ag-Industrial Multipurpose Tractors

Steel belted radial tire for industrial, construction and road works applications. The deep tread design provides excellent traction. Wear resistant tread compound provides longer service life. The unique bead design gains better airtightness for tubeless tires.



Item number	Size	LI/SI	Tube Type	ECE	Rim Width (inch)	Mounted Diameter (mm)	Mounted Width (mm)	Max Load (kg)	Rated Speed (km/h)	Inflation Pressure (bar)	Tread depth (mm)	Weight (kg)	CoO	EAN
6X16441	460/70R24 (17.5LR24)	159A8/B	TL	YES	DW15L	1254	455	4375	50	4	36	94.8	CN	5999110834603
6X16451	500/70R24 (19.5LR24)	164A8/B	TL	YES	DW16L	1310	503	5000	50	4	38	115.45	CN	5999110834610

GROUND FORCE 750

Backhoe loader, industrial tractors

Ground Force 750 is a radial backhoe tire designed with updated profile for more comfortable ride on hard surface.



Item number	Size	PR	LI/SI	Tube Type	ECE	Rim Width (inch)	Mounted Diameter (mm)	Mounted Width (mm)	Max Load (kg)	Rated Speed (km/h)	Inflation Pressure (bar)	Tread depth (mm)	Weight (kg)	CoO	EAN
6X20511	460/70R24 (17.5LR24)		159A8/159B	TL	YES	DW15L	1254	455	4375	50	4	32	103	CN	5999110840000
6X21301	500/70R24 (19.5LR24)		164A8/164B	TL	YES	DW16L	1310	503	5000	50	4	35	122,7	CN	5999110834610

GROUND FORCE 801

Wheeled Excavator

Applicable for excavator and rough surface transporters with unique Off-road tread pattern design providing excellent traction and puncture resistance performance.



Item number	Size	PR	LI/SI	Tube Type	Rim Width (inch)	Mounted Diameter (mm)	Mounted Width (mm)	Max Load (kg)	Rated Speed (km/h)	Inflation Pressure (bar)	Tread depth (mm)	Weight (kg)	CoO	EAN
6X16411	8.25-20	14	134/B	SET	6.5	995	235	2120	50	7.4	17	35.88	CN	5999110834573
6X16421	9.00-20	16	143/B	SET	7	1018	259	2725	50	8.1	20	44.19	CN	5999110834580
6X16431	10.00-20	16	146/B	SET	7.5	1055	278	3000	50	7.5	19	44.96	CN	5999110834597

SET=tire+tube+flap

GROUND FORCE 850 E

Excavator and forestry tire

Ground Force 850E is a steel belted 24 PR strong construction with maximal puncture resistance. Open V Shape design for maximum pull force. HD Version with thick sidewalls ensures a high stability.



Item number	Size	PR	LI/SI	Tube Type	ECE	Rim Width (inch)	Mounted Diameter (mm)	Mounted Width (mm)	Max Load (kg)	Rated Speed (km/h)	Inflation Pressure (bar)	Tread depth (mm)	Weight (kg)	CoO	EAN
6X20051	600/50-22.5	24	173A8	TL	YES	20	1151	601	6500	40	6	42	167	CN	5999110838779
6X20061	650/45-22.5	24	175A8	TL	YES	20	1153	635	6900	40	6	45	187	CN	5999110838786
6X20071	710/40-22.5	24	173A8	TL	YES	24	1151	700	6500	40	5.5	42	187	CN	5999110838793

GROUND FORCE 901

Multipurpose Loaders, Backhoe, Agro-Industrial

A steel belted tire with a large tread blocks for traction and wear performance. The tire has good self-cleaning ability and robust construction.



Item number	Size	LI/SI	Tube Type	Rim Width (inch)	Mounted Diameter (mm)	Mounted Width (mm)	Max Load (kg)	Rated Speed (km/h)	Inflation Pressure (bar)	Tread depth (mm)	Weight (kg)	CoO	EAN
6X16461	405/70R18	141B/153A2	TL	11.00	1020	400	2575/3650	50/10	3.8	20	63.25	CN	5999110834627
6X16471	405/70R20	143B/155A2	TL	13.00	1090	400	2725/3875	50/10	3.8	20	70.93	CN	5999110834634
6X16481	405/70R24	146B/158A2	TL	13.00	1170	400	3000/4250	50/10	3.8	20	79.96	CN	5999110834641

GROUND FORCE 400 MX

Skid steer, loaders application

Strong traction tread with robust construction. Robust sidewall design, robust tread compound for general duty skid steer applications



Item number	Size	PR	LI/SI	Tube Type	ECE	Rim Width (inch)	Mounted Diameter (mm)	Mounted Width (mm)	Max Load (kg)	Rated Speed (km/h)	Inflation Pressure (bar)	Tread depth (mm)	Weight (kg)	CoO	EAN
6X17063	10-16.5	10		TL		8.25	814	259	2120	10	5.2	37.3	40.3	IND	5999110837239
6X17073	12-16.5	14		TL		9.75	858	310	3075	10	6.2	37.3	51.8	IND	5999110837260

GROUND FORCE 400 ULTRA

Skid steer, loaders application

The Ground Force® 400 Ultra is a severe service skid steer tire. Its tread depth is 70% deeper than other premium skid steer tires and yields a 14% longer service life. With a thick sidewall buff bar for extra abrasion protection, is proven to provide absolute durability. The Ground Force® 400 Ultra is a substitute for Ultra Guard.



Item number	Size	PR	LI/SI	Tube Type	ECE	Rim Width (inch)	Mounted Diameter (mm)	Mounted Width (mm)	Max Load (kg)	Rated Speed (km/h)	Inflation Pressure (bar)	Tread depth (mm)	Weight (kg)	CoO	EAN
6X17063	10-16.5	10		TL		8.25	814	259	2120	10	5.2	37.3	40.3	IND	5999110837239
6X17073	12-16.5	14		TL		9.75	858	310	3075	10	6.2	37.3	51.8	IND	5999110837260

GROUND FORCE 400 R4

Skid steer, loaders application

Strong traction tread with robust construction.



Item number	Size	PR	LI/SI	Tube Type	ECE	Rim Width (inch)	Mounted Diameter (mm)	Mounted Width (mm)	Max Load (kg)	Rated Speed (km/h)	Inflation Pressure (bar)	Tread depth (mm)	Weight (kg)	CoO	EAN
6X19813	5.70-12	4	93A2	TL		4.5E	570	140	650		4	13.5	7.9	IND	5999110838625
6X17763	18x8.50-10	4		TL		7	462.3	206	375	10	1.5	12.7	6.8	IND	5999110837178
6X17803	23x8.50-12	6		TL		7	574	208	825	10	3.45	11.1	11.9	IND	5999110837185
6X17773	25x8.50-14	6		TL		7	655.3	211	975	10	3.45	13.5	12.9	IND	5999110837192
6X17793	27x8.50-15	6		TL		7	678.2	213	1090	10	3.1	13.5	16.5	IND	5999110837208
6X17783	27x10.50-15	6		TL		8.5	680.7	264	1180	10	3.1	13.5	16.4	IND	5999110837215
6X17213	10-16.5	10		TL		8.25	778	264	2120	10	5.2	16.7	22.7	IND	5999110837222
6X17243	12-16.5	12		TL		9.75	830	305	2867	10	5.5	19.8	32.14	IND	5999110837253
6X17743	14-17.5	14		TL		10.5	916.9	345	3875	10	5.5	19.8	38.2	IND	5999110837284
6X17753	15-19.5	14		TL		11.75	1008.4	389	4500	10	4.8	20.6	62.5	IND	5999110837291

GUARD DOG HD

General Duty Skid Steer And Compact Tractor Applications

Designed for heavy-duty skid steers, the Guard Dog HD tire has premium tread compounds for tougher service conditions and rigorous construction applications. With its stepped-off outer tread lugs and squared shoulder design, the Guard Dog HD delivers maximum performance and stability on the work site. Made in the USA.



Item Number	Size	PR	LI/SI	Tube Type	Rim Width (inch)	Mounted Diameter (mm)	Mounted Width (mm)	Max Load (kg)	Rated Speed (km/h)	Inflation Pressure (bar)	Tread depth (mm)	Weight (kg)	CoO	EAN
570031	33x15.50-16.5	12	148/A2	TL	12	833.1	366	3100	10	4.15	22.2	44	US	5999110803685

XTRA GRIP R-4

Backhoe And Industrial Application

The Xtra Grip R4 tire provides excellent traction for turf and sod applications. This all-purpose farm or industrial tractor tire is engineered with a compound to resist cutting and penetration. It also has a rugged, heavy-duty construction to withstand rigorous operating site conditions.



Item Number	Size	PR	LI/SI	Tube Type	ECE	Rim Width (inch)	Mounted Diameter (mm)	Mounted Width (mm)	Max Load (kg)	Rated Speed (km/h)	Inflation Pressure (bar)	Tread depth (mm)	Weight (kg)	CoO	EAN
570059	43x16.00-20	6	129/A8	TL	YES	14	1094.7	424	1850	40	2.1	21.4	53.15	US	5999110804354

TRAC CHIEF

Skid Steer, Backhoe, Subcompact Tractor

The Trac Chief tire delivers diverse capabilities of aggressive and durable traction on soft surfaces while still providing a smooth ride. It's directional tread design and high load capacity brings stability and easy steering.



Item Number	Size	PR	LI/SI	Tube Type	ECE	Rim Width (inch)	Mounted Diameter (mm)	Mounted Width (mm)	Max Load (kg)	Rated Speed (km/h)	Inflation Pressure (bar)	Tread depth (mm)	Weight (kg)	CoO	EAN
560483	20x8.00-10	4	77/A3	TL		7	490,2	208	412	15	1,65	12,7	7,97	US	5999110804163
51S3C2	5.70-12 NHS (140/90-12)	4	93/A2	TL	YES	4,5	569	140	650	10	4,15	13,5	7,22	US	5999110825137
6A0282	26x12.00-12 NHS 8PR TL Trac Chief	8		TL		10,5	653	320	1370	10	3,5	15,1	19,7	US	5999110836607
51S388	23x8.50-14 SS NHS (215/55-14 SS)	4	94/A2	TL	YES	7	584,2	203	670	10	2,4	13,5	10	US	5999110800554
560369	27x10.50-15	8	126/A2	TL		8,5	678,2	259	1700	10	4,15	13,5	18,27	US	5999110825700
570139	28x8.50-15 NHS	6	102/A2	TL		7	717,6	222	850	10	3,1	12,7	14,48	US	5999110825489
51S3D1	10-16.5 NHS	8		TL		8,25	774,7	272	1878	10	4,15	15,1	20,2	US	5999110804101
5701401	10-16.5 NHS	10		TL		8,25	776	274	2136	10	5,2	15,1	23,3	CN	5999110804095
511703	385/65D19.5 (15.00D19.5 NHS)	16	164/A2	TL		12,25	1017,3	414	5000	10	6,55	19,8	52,5	US	5999110804224
570122	12.4-16	6	110/A8	TL		11	950	338	1060	40	2,1	23,8	37,11	US	5999110804118

ULTRA GUARD MX

General Duty Skid Steer

The Ultra Guard MX tire is engineered for Severe Duty skid steer applications. Designed with a unique large angled, non-directional center lug tread design, the Ultra Guard MX delivers increased performance on soft and hard surfaces. Made in the USA.



Item Number	Size	PR	LI/SI	Tube Type	Rim Width (inch)	Mounted Diameter (mm)	Mounted Width (mm)	Max Load (kg)	Rated Speed (km/h)	Inflation Pressure (bar)	Tread depth (mm)	Weight (kg)	CoO	EAN
6A0327	14-17.5	14	155/A2	TL	10.5	914.7	366	3874	10	5.5	33.3	52.94	US	5999110804293

USA LOADER

Skid Steers, Aerial Platform Lifts And Backhoe Loaders

Engineered with lateral grooves and a "Boot Heel Lug" tread conguration, the USA Loader brings traction and stability on specialty applications where safety and stability are critical.



Item Number	Size	PR	Tube Type	Rim Width (inch)	Mounted Diameter (mm)	Mounted Width (mm)	Max Load (kg)	Rated Speed (km/h)	Inflation Pressure (bar)	Tread depth (mm)	Weight (kg)	CoO	EAN
6A0170	305/70D16.5 NHS	10	TL	9.75	835.7	320	2540	10	4.5	21.4	35	US	5999110804323

GROUND FORCE ULTRA RIB GSE

Compaction and Road Paving Equipments, Material Handling Equipments, Mining

Combined with a sturdy rib tread pattern and premium tread compounds, the Ground Force Ultra Rib GSE tire is specially designed for optimal performance on ground support equipment.



Item number	Size	PR	Tube Type	Rim Width (inch)	Mounted Diameter (mm)	Mounted Width (mm)	Max Load (kg)	Rated Speed (km/h)	Inflation Pressure (bar)	Tread depth (mm)	Weight (kg)	CoO	EAN
60108	9.00-10 NHS	10	TT	6	691	246	1520	15	5.8	7.1	16	US	5999110806761

ROAD ROLLER

Compaction and Road Paving Equipment

The Road Roller tire offers a smooth and steady tread for a consistent and leveled ride. With superior heat resistant nylon fabric belts, this tire supports heavy-duty handling with effortless execution.



Item Number	Size	PR	Tube Type	Rim Width (inch)	Mounted Diameter (mm)	Mounted Width (mm)	Max Load (kg)	Rated Speed (km/h)	Inflation Pressure (bar)	Tread depth (mm)	Weight (kg)	CoO	EAN
60127	7.50-15	12	TT	6	784.9	218	2658	15	7.6	0	19.7	US	5999110806846

INDUSTRIAL ALL PURPOSE

Material Handling Equipments

Designed with two different rib patterns throughout the tread, the Industrial All Purpose tire presents a multi-purpose service of both traction and support with optimized weight distribution for stability with heavy equipment.



Item Number	Size	PR	Tube Type	Rim Width (inch)	Mounted Diameter (mm)	Mounted Width (mm)	Max Load (kg)	Rated Speed (km/h)	Inflation Pressure (bar)	Tread depth (mm)	Weight (kg)	CoO	EAN
60129	7.50-10 NHS	10	TT	6	637.5	209	1383	15	6.9	9.5	11	US	5999110806877
60100	7.50-10 LRE	10 (LRE)	TT	5.5	642.6	193	896	100	6.2	9.5	11	US	5999110806860

PREMIUM WIDE TRAC

Material Handling Equipments

The Premium Wide Trac tire offers superior level design with an extra heavy-duty sidewall for material handling applications. Its durable construction resists abrasions in severe conditions to maximize efficiency.



Item Number	Size	PR	Tube Type	Rim Width (inch)	Mounted Diameter (mm)	Mounted Width (mm)	Max Load (kg)	Rated Speed (km/h)	Inflation Pressure (bar)	Tread depth (mm)	Weight (kg)	CoO	EAN
60118	5.70/5.00-8 NHS	8	TT	3	469.9	140	875	15	8.25	13.5	6.8	US	5999110806938
60120	28x9.00-15	14	TT	7	693.4	224	3121	15	8.25	14.3	24.3	US	5999110807058
60119	28x9.00-15	12	TT	7	693.4	226	3416	15	9.65	14.3	23.91	US	5999110806945
60115	28x12.00-15	20	TT	9.75	713.7	292	4899	15	10.35	19.1	39.03	US	5999110806914

INDUSTRIAL DEEP TRACTION

Material Handling Equipments

With its flat tread and reinforced beads, the Industrial Deep Traction tire is an essential standard duty tire that delivers stability and long lasting performance.



Item Number	Size	PR	Tube Type	Rim Width (inch)	Mounted Diameter (mm)	Mounted Width (mm)	Max Load (kg)	Rated Speed (km/h)	Inflation Pressure (bar)	Tread depth (mm)	Weight (kg)	CoO	EAN
60101	6.90/6.00-9 NHS	10	TT	4	556.3	175	1685	15	8.6	15.1	9	US	5999110806785

GROUND FORCE 200 & 202

Material Handling Equipments

The Ground Force 200, industrial pneumatic tire features a heavy-duty design for tough applications. Sipes in the shoulder lugs enhance heat dissipation. Reinforced sidewall for reduced deflection and improved protection. Wider tread profile for improved traction and lateral stability [GF 202]. Rim guard protects bead area in rugged applications.



SKU	Size	PR	Tread Type	Mounted Diameter (mm)	Mounted Section Width (mm)	Rim Width (inch)	Inflation Pressure (bar)	Load Capacity (kg)			Tread depth (mm)	Weight (kg)	CoO	EAN
								- Forklift	- Up to 25 Km/h	Side Loader				
XA4A047	16x6.00-8 TT SET	18	200	420	158	4.33	10.5	1540	1185	1790	12.5	8.1	IN	5999110832531
XA4A048	18x7.00-8 TT SET	14	200	462	170	4.33	9	1910	1460	2400	17	10.0	IN	5999110832555
XA4A049	18x7.00-8 TT SET	16	200	462	170	5.33	10	2145	1650	2490	17	10.9	IN	5999110832562
XA4A050	18x7.00-8 TT SET	18	200	462	170	6.33	10.5	2210	1700	2565	17	10.9	IN	5999110832579
XA4A033	5.00 - 8 TT SET	8	202	473	135	3	8.25	1235	950	1435	12.5	6.9	IN	5999110832586
XA4A034	5.00 - 8 TT SET	10	200	470	145	3	10	1415	1090	1645	13	7.7	IN	5999110832593
XA4A051	21x8.00-9 TT SET	16	200	535	210	6.00	10	2755	2120	3200	18	16.7	IN	5999110832609
XA4A035	6.90/6.00 - 9 TT SET	10	202	540	160	4	8.5	1715	1320	1990	14	9.9	IN	5999110832616
XA4A036	6.00-9 TT SET	12	200	540	165	4	10	1885	1450	2190	15.5	11.3	IN	5999110832623
XA4A052	23x9.00-10 TT SET	18	200	590	235	7.00	9	3160	2430	3670	18.5	22.3	IN	5999110832630
XA4A053	23x9.00-10 TT SET	20	200	590	235	8.00	10	3445	2650	4000	18.5	22.3	IN	5999110832647
XA4A037	6.50 - 10 TT SET	10	202	600	185	5	7.75	1950	1500	2260	15.5	12.1	IN	5999110832654
XA4A038	6.50 - 10 TT SET	12	200	598	190	5.00	9	2145	1650	2490	15.5	16.0	IN	5999110832661
XA4A039	6.50 - 10 TT SET	14	200	598	190	5.00	10	2340	1800	2650	15.5	15.5	IN	5999110832678
XA4A056	23x10.00-12 TT SET	18	200	605	260	8.00	9	3385	2605	3935	15.5	24.4	IN	5999110832685
XA4A040	7.00-12 TT SET	12	200	680	196	5	8.5	2680	2060	3110	15.5	19.7	IN	5999110832692
XA4A042	7.00-12 TT SET	16	200	680	196	5.00	10	2910	2240	3400	15.5	20.5	IN	5999110832708
XA4A041	7.00-12 TT SET	14	202	685	195	5.00	9	2755	2120	3200	16.8	17.2	IN	5999110832715
XA4A054	27x10.00-12 TT SET	12	200	692	252	8.00	7.25	3250	2470	4275	21.5	27.1	IN	5999110832722
XA4A055	27x10.00-12 TT SET	16	200	692	252	9.00	8	3900	3000	4530	21.5	29.3	IN	5999110832739
XA4A043	8.15-15 TT SET	12	200	725	219	7.00	8.25	3445	2650	4000	18	24.3	IN	5999110832746
XA4A044	8.15-15 TT SET	14	202	715	219	7.00	10	3900	3000	4530	19	24.1	IN	5999110832753
XA4A045	8.15-15 TT SET	16	200	725	219	7.00	10.5	4010	3085	4660	18	26.6	IN	5999110832760
XA4A062	250-15 TT SET	16	200	747	250	7.00	8.25	4355	3350	5060	18	34.4	IN	5999110832777
XA4A057	7.00-15 TT SET	12	200	750	200	5.50	8.25	3070	2360	3565	18	25.1	IN	5999110832784
XA4A058	7.00-15 TT SET	14	200	750	200	6.50	9.25	3280	2525	3810	18	25.1	IN	5999110832791
XA4A059	7.00-15 TT SET	16	200	750	200	7.50	10	3545	2725	3990	18	25.1	IN	5999110832807
XA4A060	7.50-15 TT SET	14	200	780	218	6.00	9.25	3640	2800	4230	18	26.4	IN	5999110832814
XA4A061	7.50-15 TT SET	16	200	780	218	7.00	10	3810	2930	4425	18	28.6	IN	5999110832821
XA4A063	300-15 TT SET	16	200	840	300	8.00	6	5130	3945	5955	22	46.1	IN	5999110832838
XA4A064	300-15 TT SET	18	200	840	300	9.00	7.5	5845	4495	6785	22	48.8	IN	5999110832845
XA4A065	300-15 TT SET	20	200	840	300	10.00	9	6500	5000	7550	22	48.8	IN	5999110832852
XA4A066	8.25-15 TT SET	14	200	840	235	6.50	8	4225	3250	4910	21	40.0	IN	5999110832869
XA4A067	8.25-15 TT SET	16	200	840	235	7.50	9.25	4615	3550	5345	21	40.0	IN	5999110832876
XA4A046	8.25-15 TT SET	14	202	845	240	6.5	8	4225	3250	4910	18	31.4	IN	5999110832883

SET=tire+tube+flap

CARLISLE

branded tires are now

CARLSTAR



The content and information in the Catalogue is provided as information to the interested persons and may be used for informational purposes only. Information on products may pertain to limited geographic areas and markets. A reference to a product in the Catalogue does not imply that such product is, remains or will be available in the reader's location. None of the content and information in the Catalogue may be deemed to constitute an offer by Titan Distribution Europe Kft. Titan Distribution Europe Kft makes every effort to maintain the accuracy and quality of the information provided in the Catalogue. However, Titan Distribution Europe Kft. cannot guarantee and assumes no legal liability or responsibility for the accuracy or completeness of the information provided in the Catalogue. Titan Distribution Europe Kft. assumes no legal liability or responsibility for printing errors. It is the reader who assumes the risk that the information in the Catalogue may be incomplete, inaccurate, out of date or it may not meet the reader's needs and requirements.

www.carlstartires.eu